

# PLACCEL 210B


Polycaprolactone diol with narrow molecular weight distribution

## <Description>

PLACCEL 210B is a specially designed polycaprolactone diol for millable polyurethane.

The cured millable polyurethane used PLACCEL 210B show excellent abrasion resistance, a low temperature property, good mechanical property and good hydrolysis resistance.

The recommended applications of the polyurethane elastomers are rolls, seals, gasket, O-rings and belts.



## <Composition / Information on ingredients>

Composition of Polycaprolactone diol (PLACCEL 210B)

Chemical Name & CAS No.	Composition & % (Typical)	Lot No.
Polycaprolactone diol	100%	20170114

For the safety handling method, please refer to the label and the instruction sheet.

## Global Regulation

RoHS	REACH	SVHC	Phthalates	PAHs	PCP	PCB	PFOS	PFOA	Phthalates	Phthalates
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

For detailed information, please refer to the label.

## Typical properties

Grade	Molecular Weight (g/mol)	Inherent Viscosity (dl/g)	Inherent Viscosity (dl/g)			Inherent Viscosity (dl/g)	Inherent Viscosity (dl/g)
			25°C	30°C	35°C		
PLACCEL 210B	100,000	0.8	0.5	0.3	0.2	0.1	0.05

It should be noted that typical property values shown in this technical data sheet are representative values and are not guaranteed values. Please contact us to obtain actual product and guaranteed values.

Please refer to our SDS safety data sheet for information on the handling of each product.

**DAICEL CORPORATION**

Global Chemicals Division

Performance Products Marketing

4F Shingon 2nd Bldg, 2-1-1, Fussa, Tokyo

Japan 188-8501

PLACCEL 210B  
PLACCEL 210B  
PLACCEL 210B