


PLACCEL 220UA

Polycaprolactone diol

<Description>

PLACCEL 220UA is polycaprolactone diol and its molecular weight is 2000. In particular, PLACCEL 220UA is characterized by its higher meltability than other PLACCEL 220 series.

PLACCEL 220UA is mainly used as modifying agent for polyurethane, such as urethane adhesive, urethane binder and urethane elastomer. Especially, polyurethane made from PLACCEL 220UA has excellent properties in durability, hydrolysis resistance, oil resistance, heat resistance and low temperature characteristics.



<Composition / Information on ingredients>

Composition of Substances in Weight Substances

Chemical Name of Substances	Composition of % Weight	Unit (%)
Polycaprolactone diol	100%	1000000

Global Regulations

RoHS	REACH	SVHC	Phthalates	PAHs	PFOS	PFOA	Phthalates	Phthalates	Phthalates
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

(*) The above information is not intended to be a guarantee.

Typical properties

Item	Unit	Value	Reference	Density (g/cm ³)			Tensile strength (MPa)
				25°C	30°C	40°C	
PLACCEL 220UA	g/cm ³	1.14	1.14	1.14	1.14	1.14	1.14

It should be noted that typical property values shown in the technical data sheet are representative values and are not guaranteed values. Please contact us to obtain detail of product and guaranteed values.

Please refer to our SDS (Safety Data Sheet) for information on the handling of each product.

DAICEL CORPORATION

Chemical Division, Polycaprolactone Division
Organic Chemical Marketing Group
4-1-1 Higashi, Suita, Osaka 565-0821, Japan
Tel: 81-6-6543-1111

PLACCEL 220UA
PLACCEL 220UA
PLACCEL 220UA