


PLACCEL 240CP

Polycaprolactone diol

<Description>

PLACCEL 240CP is polycaprolactone diol and its molecular weight is 4000. Since it is manufactured by ring opening polymerization of epsilon-caprolactone, exact control of hydroxyl group value is possible. PLACCEL 240CP is mainly used as soft-segment of polyurethane, such as thermoplastic polyurethane elastomer, thermosetting polyurethane elastomer, urethane adhesive and urethane binder and so on.



<Composition / Information on ingredients>

Composition of Polycaprolactone diol, Polycaprolactone

Chemical Name / Japanese Name	Concentration / % Weight	Lot No.
Polycaprolactone diol	100%	20190073

Global Regulations

RoHS	REACH	SVHC	Phthalates	PAHs	PFOS	PFOA	Fluorinated	Phthalates	Phthalates	Phthalates
✓	✓	✓	✓	✓	✓	✓		✓	✓	✓

RoHS: Complies with RoHS (Restriction of Hazardous Substances) / REACH

Typical properties

Item	Unit	Value	Density (g/cm ³)			
			25°C	30°C	40°C	50°C
PLACCEL 240CP	g/cm ³	1.14	1.14	1.13	1.12	1.11

It should be noted that typical property values shown in the technical data sheet are representative values and are not guaranteed values. Please contact us to obtain detail of product and guaranteed values.

Please refer to our SDS (Safety Data Sheet) for information on the handling of each product.

DAICEL CORPORATION

Chemical Division, Performance Products Group
Performance Products Marketing Group
4-1-1, Honjo, Bunkyo-ku, Tokyo 112-8580, Japan

TEL: 03-3211-8111
TEL: 03-3211-8112
E-MAIL: daicel@daicel.com